



Main

Range of product	Actassi
Product or component type	Patch panel
Device application	Communication
Device presentation	Loaded
Provided equipment	With RJ45 connectors Rear cable manager Front label holder 3 Cable fixing hardware Mounting hardware Retaining cap With shutter
Colour tint	Front plate blue glossy
Colour code	568 A/B

Complementary

[In] rated current	1.5 A
Rated voltage	72 V DC
Dielectric strength	1000 V for 1 min at 60 Hz
Contacts material	Modular connector: phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel IDC connector: phosphor bronze with nickel plating
Number of port	24 port of UTP
Product compatibility	standard 19" cabinet/rack
AWG gauge	AWG 24...AWG 22
Cable outer diameter	0.9...1.22 mm
Communication network category	6
Contact resistance	20 mOhm
Insulation resistance	>= 200 MOhm
Minimum number of matings	750 cycles
Number of rack unit	1U
Plug, socket, control station shape	Straight
Surface finish	Powder coated
Type of connector	S-110 keystone
Type of connector	Asia Pacific

Environment

Ambient air temperature for operation	-40...70 °C
Ambient air temperature for storage	-20...60 °C
Relative humidity	0...93 %
Flame retardance	UL94-V0
Standards	ISO/IEC 11801 Ed.2, 2002 ANSI/TIA-568-C.2 IEC 60603-7
Product certifications	UL listed ETL verified

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins