



Main

Range	Actassi
Product brand	Schneider Electric
Product type	Keystone modular jack
Provided equipment	Without shutter
Colour tint	White
Wiring Colour configuration	TIA-568A/B
Type of packing	Plastic bag and carton
Quantity per set	Set of 1

Complementary

[In] rated current	1.5 A at 25 °C
Voltage proof	1000 V AC/DC peak, between contacts
Contact resistance	20 mOhm
Insulation resistance	>= 500 MOhm
Connector type	RJ45
AWG gauge	AWG 24...AWG 22
Durability	1000 cycles
Tool type	Punch down tool Quick termination tool
Cable outer diameter	0.7...1.4 mm
Compatible LAN cable types	UTP
Communication network category	6
Supported applications	1000BASE-T
Product compatibility	RJ45 plug RJ11 plug
Type of footprint	S-110 keystone
Type of footprint	Asia Pacific

Environment

Operational temperature range	-10...60 °C
Ambient air temperature for storage	-20...70 °C

Climatic category	40/070/21 (21 days)
Flame retardance	UL94-V0 conforming to UL listed
Environmental characteristic	REACH RoHS compliant
Product certifications	FCC part 68 F IEC 60603-7
Standards	IEC 11801 class E

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------